



INDICATIVE PHOTO

General features : ERM145Z0212

- Self-supporting casing in steel varnished with epoxy powder
- Sound insulation
- Hermetic reciprocating compressor
- Crankcase heater
- Curved condenser made of copper tube and aluminium fins
- Condenser fan speed variator
- Axial fan motor (230V/1/50Hz) low speed (900 rpm)
- Liquid receiver
- Drier filter
- Sight glass
- Dual pressure switch with manual or automatic reset
- Condensing unit under nitrogen pressure
- Service valves for liquid and suction lines
- Connections to be welded
- Built-in electrical box equipped with disconnecting switch
- The fan-motors in use comply with ErP directive (Regulation EU 327/2011)
- Package included
- The conditions of calculation of the absorptions are T. cond. = 50°C; Te = -10°C (MBP); Te = -20°C (LBP)



Indicative photo

Product file : Condensing units with housing

Code	ERM145Z0212
Range	ME
Application	MBP
Condensation	Air
Expansion	Valve
Gas	R404A
Net weight	89 kg
Liquid diam.	10 mm
Suction diam.	16 mm
Noise	42 dBa 10m

Sizes

Width L	1156 mm
Depth P	420 mm
Height H	785 mm

Absorptions

Power consumption	1919 W
Current consumption	4,2 A


Condenser

Fans no.	1
Diameter	450 mm

Compressor

Type	Hermetic
Voltage	400/3/50
Displacement	43,5cm ³

Technical drawing - ERM145Z0212



Refrigerating capacity table (watt)

Ta \ Te	-15°C	-10°C	-5°C	0°C
32°C	2741	3451	4225	5059
43°C	2052	2659	3310	4001

Per condizioni di calcolo diverse da quelle riportate in tabella contattare l'ufficio tecnico

Descrizioni, dati tecnici ed illustrazioni sono indicativi e non vincolanti. La Rivacold si riserva il diritto, di modificare per intero o in parte le specifiche tecniche descritte nella presente documentazione senza preavviso e a beneficio della continuità produttiva, di utilizzare produttori alternativi di componenti previsti nel progetto.