



### Applications

O16 instruments are single mechanical pressure switches for high and low pressure, equipped with a single pole switch SPDT that closes and opens as the pressure increases or decreases.

### Common features

### O16 pressure

SPDT single pole switch electrical rating:	16 (16) A 250V~ normally open or normally closed 1 (1) A 250V~ opposite side.
Ambient operating/storage temperature:	-30°C...+55°C / -40°C...+65°C
Connection to pressure line:	7/16 - 20 UNF straight male output connector, 1/4 flared female connector
Cable entry:	14mm insulating bushing
Refrigerant:	Equipment suitable for use with the most common gases
Installation:	two threaded holes in the back of the casing to accept M4x6mm screws (supplied)
Regulation:	by means of crosshead recessed hex nut for both the set and the differential. An adjustable knob is also available, as standard with certain models.
Terminals:	1 common; 2 opens when the pressure increases; 4 closes when the pressure increases.
Casing enclosure rating:	IP44 (with top cover installed)

### Operating and safety

Bellows type	Maximum stationary pressure (bar)	Burst Pressure (bar)
Low Pressure	20	80
High Pressure	35	128
TÜV	35	80 (safety)

Part number	High or Low	Reset	Measurement range PSI (bar)	Differential	Type of bellows	Connection
O16-H6703	low	automatic	10"...100 (-0.3...7)	9...58 (0.6...4)	standard	7/16" - 20 UNF male
O16-H6705	low	manual	10"...100 (-0.3...7)	9 (0.6)	standard	7/16" - 20 UNF male
O16-H6750	high	automatic	100...435 (7...30)	35...115 (2...8)	standard	7/16" - 20 UNF male
O16-H6751	high	manual	100...435 (7...30)	45 (3.2)	standard	7/16" - 20 UNF male

### Dimensions

