

Model: AGB2513ZTZ (TAG2516Z)
Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	7276	1834	2132	2571	2.83	.71	.83	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)
EN12900	400V 3~ 50HZ	6218	1567	1822	2106	2.95	.74	.87	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

General

Evaporating Temp. Range: N/A
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 44
Weight Unit of Measure: KG
Displacement (cc): 112.5
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 1960

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 42.5
Rated Load Amps (RLA 50 Hz): 4.8
Rated Load Amps (RLA 60 Hz): 4.9
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: N/A
Motor Resistance (Ohm) - Start: N/A
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

**CCC Listed, CE Listed, IRAM Listed, SASO Listed,
VDE Listed**